

Fast. Smart. Clean.



Union K Series

NOW THERE IS ONE SYSTEM
FOR ALL ALTERNATIVES!



The Ideal Drycleaning System For Alternative Solvents.



Technical Specifications

		Kg	HXL8018S-K	HXL8025S-K	Lbs	HXL8018S-K	HXL8025S-K
FÜLLMENGE	LOAD CAPACITY		18	25		40	55 ÷ 60
TROMMEL	BASKET						
Inhalt	Volume	lt	340	500	cu.ft.	12	17.7
Durchmesser	Diameter	mm	900	1000	inches	35.4	39.4
Tiefe	Depth	mm	535	640	inches	21	25.2
Reinigungsdrehzahl	Wash speed	rpm	12 ÷ 50	12 ÷ 50	rpm	12 ÷ 50	12 ÷ 50
Schleuderdrehzahl	Extract speed	rpm	300 ÷ 520	300 ÷ 520	rpm	300 ÷ 520	300 ÷ 520
Ladetürdurchmesser	Door opening	mm	500	500	inches	20	20
TANKVOLUMEN	TANKS						
1. Tank	Useful volume tank 1	lt	118	145	gal	31	38
2. Tank	Useful volume tank 2	lt	118	145	gal	31	38
3. Tank	Useful volume tank 3	lt	160	190	gal	42	52
DESTILLATION	STILL						
Nutzinhalt	Useful Still Volume at half inspection	lt	145	190	gal	38,3	50
Gesamtinhalt	Total Still Volume	lt	180	230	gal	47,6	61
SCHLEUDERFILTER	NYLON FILTER						
Inhalt	Volume nylon filter housing	lt	55	55	gal	14.5	14.5
Oberfläche	Nylon filter area	mt ²	3,9	3,9	ft ²	42	42
Filterscheiben	Filter disks	nr	26	26	nr	26	26
DEKO-FILTER	PURITAN FILTER						
Filterinhalt	Volume Puritan filter housing	lt	13	13	gal	3.5	3.5
Rohr	Tubes numbers	nr	1	1	nr	1	1
Kartusche	Cartridges quantity	nr	1	1	nr	1	1
KARTUSCHENFILTER	DUAL CARTRIDGE FILTER						
Filterinhalt	Volume Dual cartridge filter housing	lt	55	55	gal	14.5	14.5
Rohr	Tubes numbers	nr	1	1	nr	1	1
Kartusche	Cartridges quantity	nr	2	2	nr	2	2
STROMLEISTUNG (400V 3ph 50Hz)	ELECTRIC POWER (400V 3ph 50Hz)						
Reinigungs- und Schleudermotor – inverter	Wash / Extract motor - with Inverter *	Kw	1,3 ÷ 3,5	2 ÷ 5,5	Hp	4,7	7.5
Lösemittelpumpe	Solvent pump motor	Kw	0,75	0,75	Hp	1	1
Ventilator	Fan motor	Kw	1,5	1,5	Hp	3.5	3.5
Kühlkompressor	Refrigerator compressor	Kw	3,75	3,75	Hp	5	5
Schleuderfilter	Nylon filter motor	Kw	0,55	0,55	Hp	0.75	0.75
Vakuumpumpe	Vacuum Pump Motor	Kw	0,38	0,38	Hp	0.5	0.5
Heizstäbe	Heater electric elements	Kw	9	9	Hp	9	9,5
LEITUNGSANSCHLÜSSE	CONNECTIONS SUPPLY						
Druckluft ein	Compressed air inlet	Ø	1/4"	1/4"	Ø	1/4"	1/4"
Wasser ein	Water inlet	Ø	3/4"	3/4"	Ø	3/4"	3/4"
Wasser aus	Water outlet	Ø	3/4"	3/4"	Ø	3/4"	3/4"
Destillationsdampf und Heizung ein	Steam Still and heater inlet	Ø	1/2"	1/2"	Ø	1/2"	1/2"
Destillationskondensat und Heizung aus	Condensat Still and heater outlet	Ø	1/2"	1/2"	Ø	1/2"	1/2"
GEWICHTE	MACHINES WEIGHTS						
Leergewicht	Empty machine weight	Kg	1680	2100	lbs	3704	4630
MASCHINEMASSE	MACHINES DIMENSIONS						
(A) Breite	(A) Width front Machine	mm	1800+154	2000+154	inches	70,9+6	78,7+6
(B) Tiefe	(B) Depth	mm	1650	1900	inches	65	74,8
(C) Höhe (installiert)	(C) Height With Fan	mm	2170	2240	inches	85,4	88,2

Maschinen Lärmeniveau liegt unter 70 dB (A)

Daten können ohne Vorankündigung geändert werden.

Acoustic emission level of the machines is lower than 70 dB (A)

Specifications subject to change without notice.

Für optimale Ergebnisse in der Reiningung sowie in der Trocknung mit Klasse III Lösemitteln, stellt UNION die neue **HXL8000-K** Serie vor. Kompaktes und praktisches Design, Dank jahrelanger Erfahrung, heißt hervorragende Reinigungsergebnisse, weichere Bekleidung, buntere Farben, und leichtes Bügeln! Die neue Modelle sind mit Füllmenge von 18 oder 25kg erhältlich

UNION presents the new **HXL8000-K** series designed for an optimal cleaning and drying performance with Class III solvents. A compact and functional design, thanks to years of experience, for superior and exceptional cleaning results, with softer garments, brighter colours, easier and faster ironing. The new models are available with a loading capacity of 18kg/40LBS or 25kg/60LBS.



UNION s.p.a.
 40010 Sala Bolognese (Bologna) ITALY
 Via Labriola 4/D
 Tel.: (+39) 051.6814996
 Fax: (+39) 051.6814660
 E-mail: union@uniondcm.com
 Web page: www.uniondcm.com